

KENWOOD

NEXEDGE®

NX-5200/5300/5400

NXDN™

DMR



NEXEDGE VHF/UHF/700-800 MHz
MULTI-PROTOCOL DIGITAL & ANALOG PORTABLE RADIOS



GPS

FleetSync®

5-tone

● FEATURE HIGHLIGHTS

- **Multi-Digital** operation in NXDN, DMR and P25 (Phases 1 & 2) protocols
- **Any combination of two digital protocols** can be selected from NXDN, DMR, and P25
- **Mixed Digital & FM Analog Operation** allows intelligent migration in mixed sites and easy migration with digital radios in other sites
- **Large, Color 1.74" (240 x 180 pixels) Transflective TFT Display** for better interface even in direct sunlight and with use of polarized sunglasses.
- **Easy to follow GUI** for at-a-glance operational status checking and **Multi-line Text** to convey more information
- **4-way Directional-pad (D-pad) and 2-Position Lever Switch** for intuitive control and operation
- **Built-In GPS Receiver/Antenna** for effective fleet management
- **Bluetooth® Module built-in** for hands-free operation
- Renowned KENWOOD Audio Quality can be achieved with **Active Noise Reduction (ANR)** that utilizes built-in DSP with two microphones for suppression of ambient noise
- **Built-in 56-bit DES Encryption**
- **Optional 256-bit AES Encryption**
- **Built-in Motion Sensor** for life-critical man down detection
- **microSD/microSDHC Card Slot (up to 32GB)** for increased memory capacity for "Voice & Data"
- **IP67/68 and MIL-STD-810 C/D/E/F/G**

● GENERAL FEATURES

- 6 W (136-174 MHz) Model
- 5 W (380-470, 450-520 MHz) Models
- 3 W (700/800 MHz) Models
- Full Key Models (w/ numeric keypad) and Standard Key Models (w/o numeric keypad)
- Maximum of 4,000 CH/Radio capacity, 512 CH/Zone, 128 Zones
- AMBE+2™ Enhanced Vocoder
- 1 W Loud Speaker Audio

● DIGITAL – NXDN MODE

- Gen2 & NXDN Type-C Trunked Operation
- NXDN Conventional Operation
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Over-the-Air Programming
- Paging Call

- Emergency Call
- All Group Call
- Status Messaging
- Remote Stun/Kill
- Remote Check
- Short & Long Data Messages
- NXDN Digital Scrambler

● DIGITAL – DMR MODE

- Complies with ETSI DMR Tier II standards
- DMR Tier II, DMR Auto Slot Select & Site Roaming
- Call Interruption
- Dual-slot Direct Mode

● DIGITAL – P25 MODE

- P25 Phase 1 Conventional/Trunked Operation
- P25 Phase 2 Trunked Operation
- Talk Group ID Lists
- Individual ID Lists
- Caller ID Display
- Remote Monitor/Remote Check
- Radio Inhibit
- Encryption Key Zeroize & Retention
- P25 Over-the-Air Re-keying
- P25 Over-the-Air Programming

● ANALOG – FM MODE

- Conventional & LTR Zones
- FleetSync®/II: PTT ID ANI / Caller ID Display, Selective Group Call, Emergency Status / Text Messages
- MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check / Inhibit
- QT / DQT, 2-Tone & 5-Tone
- Built-in Voice Inversion Scrambler

● INTELLIGENT BATTERY SYSTEM

- System consists of a Li-ion or Ni-MH rechargeable battery (KNB-L1/L2/L3/N4), Rapid Charger (KSC-Y32), and Battery Reader (KAS-12/12PRO) software
- Up to 60 Rapid Chargers can be chain-connected to a PC
- KAS-12 Battery Reader software can display and manage information
- Up to 5,000 batteries can be managed at a time with the addition of optional KAS-12PRO license upgrade



Full Keypad Model

Limited Keypad Model

OPTIONAL ACCESSORIES

• KNB-L1
Li-ion BATTERY PACK, IP67/68
(7.4 V/2000 mAh)

• KNB-L2
Li-ion BATTERY PACK, IP67/68
(7.4 V/2600 mAh)

• KNB-L3
Li-ion BATTERY PACK, IP67/68
(7.4 V/3400 mAh)

• KNB-N4
Ni-MH BATTERY PACK, IP67/68
(7.2 V/2500 mAh)

• KSC-Y32
RAPID CHARGER

• KSC-32/32S
RAPID CHARGER

• KSC-326/326S
MULTIPLE CHARGER
(6-unit Rapid Rate)

• KBP-8
BATTERY CASE
(12AA Alkaline Battery)

• KRA-22
VHF HELICAL ANTENNA
(Low Profile)

• KRA-23
UHF HELICAL ANTENNA
(Low Profile)

• KRA-26
VHF HELICAL ANTENNA
(Standard Length)

• KRA-27
UHF WHIP ANTENNA
(Standard Length)

• KRA-41
VHF STUBBY ANTENNA

• KRA-42
UHF STUBBY ANTENNA

• KMC-54WD
SPEAKER MICROPHONE
• 2-mic digital noise cancelling
via the radio's DSP
• 3.5mm-diameter earphone jack
• Complies with MIL-STD 810C/D/E/F/G
• IP65/67 Dust & Water*

• KMC-42WD
SPEAKER
MICROPHONE (IP67)

• KWD-AE31
SECURE CRYPTOGRAPHIC MODULE

• KBH-11
BELT CLIP

• KPG-180AP
OTAP MANAGER

• KAS-12/12PRO
BATTERY READER
(PC Software)

*The earphone jack cap must be closed tightly

Intrinsically Safe Batteries are also available.

All accessories and options may not be available in all markets.
Contact an authorized KENWOOD dealer for details and complete list of all accessories and options.

SPECIFICATIONS

		Portable Radios		
GENERAL		NX-5200	NX-5300	NX-5400
Frequency Range		136-174 MHz	Type 1: 450-520 MHz Type 2: 380-470 MHz	RX: 763-776, 851-870 MHz TX: 763-776, 793-806, 806-825, 851-870 MHz
Max. Channels Per Radio		1024 (Up to 4000 channels with option)		
Number of Zones		128		
Max. Channels Per Zone		512		
Channel Spacing	Analog	12.5/15/20/25/30 kHz	12.5/25 kHz	12.5/25 kHz
	Digital	6.25/12.5 kHz	6.25/12.5 kHz	12.5 kHz (6.25 kHz)
Power Supply		7.5 V DC $\pm$ 20 %		
Battery Life (5-5-90/10-10-80 duty cycle)	KNB-L1 (2,000 mAh)	10 hours / 6.5 hours		
	KNB-L2 (2,600 mAh)	12.5 hours / 8.5 hours		
	KNB-L3 (3,400 mAh)	17 hours / 11 hours		
	KNB-N4 (2,500 mAh)	12 hours / 8.5 hours		
	KBP-8 (w/ AA x12)	High Power: 11 hours / 8 hours Low Power: 26 hours / 18.5 hours		
Operating Temperature		-30 °C to +60 °C		
Frequency Stability (-30°C to +60°C; +25°C Ref.)		$\pm$ 0.5 ppm		
Dimensions (W x H x D) Radio w/ Battery, Projections Not Included	KNB-L1 (2,000 mAh)	58.0 x 138.9 x 36.5 mm		
	KNB-L2 (2,600 mAh)	58.0 x 138.9 x 39.5 mm		
	KNB-L3 (3,400 mAh)	58.0 x 138.9 x 44.9 mm		
	KNB-N4 (2,500 mAh)	58.0 x 166.4 x 45.2 mm		
	KBP-8 (w/ AA x 12)	67.0 x 218.3 x 53.9 mm		
Weight	KNB-L1 (2,000 mAh)	382 g		
	KNB-L2 (2,600 mAh)	406 g		
	KNB-L3 (3,400 mAh)	449 g		
	KNB-N4 (2,500 mAh)	579 g		
	KBP-8 (w/ AA x 12)	712 g		

Specifications are measured according to applicable standards, and subject to change without notice, due to advancements in technology.

APPLICABLE MIL-STD & IP

MIL Standard	810C Methods/ Procedures	810D Methods/ Procedures	810E Methods/ Procedures	810F Methods/ Procedures	810G Methods/ Procedures
Low Pressure	500.1/I	500.2/I, II	500.3/I, II	500.4/I, II	500.5/I, II
High Temperature	501.1/I, II	501.2/I, II	501.3/I, II	501.4/I, II	501.5/I, II
Low Temperature	502.1/I	502.2/I, II	502.3/I, II	502.4/I, II	502.5/I, II
Temp. Shock	503.1/I	503.2/I	503.3/I	503.4/I, II	503.5/I
Solar Radiation	505.1/I	505.2/I	505.3/I	505.4/I	505.5/I
Rain	506.1/I, II	506.2/I, II	506.3/I, II	506.4/I, III	506.5/I, III
Humidity	507.1/I, II	507.2/I, III	507.3/I, III	507.4	507.5/II
Salt Fog	509.1/I	509.2/I	509.3/I	509.4	509.5
Dust	510.1/I	510.2/I	510.3/I	510.4/I, III	510.5/I
Vibration	514.2/VIII, X	514.3/I	514.4/I	514.5/I	514.6/I
Shock	516.2/I, II, V	516.3/I, IV	516.4/I, IV	516.5/I, IV	516.6/I, IV
Immersion	—	—	—	512.4/I	512.5/I
International Protection Standard					
Dust & Water	IP54, IP55				
Immersion	IP67, IP68*				

*Conditions: Portable radio immersed for 2 hours at a depth of 1 meter

• The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. • SD and microSD are trademarks of SD-3C, LLC in the United States, and/or other countries • AMBE+2™ is a trademark of Digital Voice Systems Inc.
• Windows® is a registered trademark of Microsoft Corporation. • NXDN™ is a trademark of JVCKENWOOD Corporation and Icom Inc. • NEXEDGE® is a registered trademark of JVCKENWOOD Corporation. • FleetSync® is a registered trademark of JVCKENWOOD Corporation.

JVCKENWOOD Singapore Pte. Ltd.

1 Ang Mo Kio Street 63 Singapore 569110

comsales@sg.jvckenwood.com

www.kenwood.com/sg

http://comms.kenwood.com



CL854M-E-2R2