



客戶圖面確認簽回章

M8(M)前鎖插板式(帶接地)

AP. Lanny		UNLESS OTHERWISE SPECIFIED TOLERANCES:
REV. A	SHEET 1/1	$X \pm 0.20$ XXX ± 0.05 $XX \pm 0.10$ ANGLE $\pm 1^\circ$



 2PIN	 3PIN	 4PIN
HGM3-M802P-13-11	HGM3-M803P-13-11	HGM3-M804P-23-11

PIN ASSIGNMENTS FRONT VIEW

- 1.MATERIAL
1-1.HOUSING: PA66 UL94V-0 ; COLOR: BLACK
1-2.CONTACT: BRASS
1-3.NUT: BRASS
1-4.SHELL: BRASS
1-5.O-RING: NBR
1-6.GROUND: PHOSPHOR BRONZE
- 2.FINISH
2-1.CONTACT: GOLD FLASH PLATED
UNDER PLATE: NICKEL
2-2.NUT: NICKEL PLATED
2-3.SHELL: NICKEL PLATED
2-4.GROUND: NICKEL PLATED
- 3.ELECTRICAL SPECIFICATION
3-1.RATED CURRENT: 4A
3-2.RATED VOLTAGE: 60V
3-3.WATERPROOF: IP67
- 4.ENVIRONMENTAL
4-1.OPERATION TEMPERATURE: -40°C~85°C