

TABLE A

HGM3-M805P-07-11	HGM3-M806P-01-11

1.MATERIAL

- 1-1.HOUSING: PA UL94V-0 ; COLOR: BLACK
 1-2.CONTACT: BRASS
 1-3.NUT: BRASS
 1-4.SHELL: BRASS
 1-5.O-RING: NBR
 1-6.GROUND: PHOSPHOR BRONZE

2.FINISH

- 2-1.CONTACT: 10 MICRO INCHES MIN. GOLD PLATED
 UNDER PLATE: NICKEL
 2-2.NUT: NICKEL PLATED
 2-3.SHELL: NICKEL PLATED
 2-4.GROUND: BIRGHT TIN PLATED

3.ELECTRICAL SPECIFICATION

- 3-1.RATED CURRENT: 2A
 3-2.RATED VOLTAGE: 30V
 3-3.WATERPROOF: IP67

4.ENVIRONMENTAL

- 4-1.OPERATION TEMPERATURE: -40°C~85°C



禾剛企業有限公司
 HOU GUN ENTERPRISE CO., LTD.

REV	DESCRIPTION	DATE
		161019

客戶圖面確認簽回章

TITLE

M8(M)90度前鎖板端DIP接地

P/N: SEE TABLE A

DWG. NO: QC7658

DR. Dan UNIT:mm

CH. Jason SCALE 1:1

AP. Lanny
 REV. A SHEET 1/1
 UNLESS OTHERWISE SPECIFIED TOLERANCES:
 X ± 0.25 XXX ± 0.05
 XX ± 0.15 ANGLE $\pm 1^\circ$

